

REGULATION (EC) No 1223/2009 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL Issue date(DD/MM/YEAR): 03/05/2023 Revision date: 09/12/2024

Version: 2.0

DECLARATION OF COMPLIANCE FOR PERFUME COMPOUNDS (DCP)

The adoption of the 7th amendement of the European Cosmetic Directive 76/768/EEC requires any cosmetic product containing any of 26 raw materials identified by the Scientific Committee on Cosmetic Products and Non-Food Products intended for Consumers as likely to cause a contact allergy when present above certain trigger levels to be declared on the package label.

ALLERGENS			
Name of common ingredients glossary	CAS-No.	Allergen % in product	
Benzyl benzoate	120-51-4	76.2	
Citronellol	106-22-9	0.0000875	
p-Anisyl alcohol	105-13-5	0.000525	
Coumarin	91-64-5	0.7	
Cinnamic aldehyde; Cinnamal	104-55-2	7.5	



CERTIFICATE OF CONFORMITY OF FRAGRANCE MIXTURES WITH IFRA STANDARDS

This certificate assesses the conformity of the fragrance mixture with IFRA Standards and provides restrictions for use as necessary. It is based only on those materials subject to IFRA Standards for the toxicity endpoint(s) described in each Standard.

This Certificate does therefore not replace a comprehensive safety assessment of the fragrance mixture.

CERTIFYING PARTY:

FRENCH COLOR & FRAGRANCE International Germany, Auggen, Mittlerer Weg 35,

CERTIFICATE DELIVERED TO:

SCOPE OF THE CERTIFICATE:

Product: SALTED CARAMEL #EU55145F

Compulsory information:

We certify that the above mixture is in compliance with the Standards of the INTERNATIONAL FRAGRANCE ASSOCIATION (IFRA), up to and including the 51 Amendment to the IFRA Code of Practice (published June, 2023) provided it is used in the following class(es) at a maximum concentration level of:

IFRA Category(ies) [see Table 10 in Guidance for the use of IFRA Standards for details]	Level of use (%)*	Product application
Category 1	0 %	Lip Products of all types (solid and liquid lipsticks, balms, clear or colored, etc.) Children's toys
Category 2	0.18666667 %	Deodorant and antiperspirant products of all types including any product with intended or reasonably foreseeable use on the axillae or labelled as such (spray, stick, roll-on, under-arm, deocologne, etc.) Body sprays (including body mist)
Category 3	0.28 %	Eye products of all types (eye shadow, mascara, eyeliner, eye make-up, eye masks, eye pillows, etc.) including eye care and moisturizer Facial make up and foundation Make-up remover for face and eyes Nose pore strips Wipes or refreshing tissues for face, neck, hands, body



RENCH COLOR & FRAGRANCE CO.		Body and face paint (for children and adults)
		Facial masks for face and around the eyes
Category 4	3.33333333 %	Hydroalcoholic and non-hydroalcoholic fine fragrance of all types (Eau de Toilette, Parfum, Cologne, solid perfume, fragrancing cream, etc.), aftershaves of all types (except creams and balms) Fragranced bracelets Ingredients of perfume kits and fragrance mixtures for cosmetic kits Scent pads, foil packs Scent strips for hydroalcoholic products
Category 5A	0.853333333 %	Body creams, oils, lotions of all types Foot care products (creams and powders) Insect repellent (intended to be applied to the skin) All powders and talc (excluding baby powders and talc)
Category 5B	0.27559055 %	Facial toner Facial moisturizers and creams (including care products for beard and mustache)
Category 5C	0.853333333 %	Hand cream Nail care products including cuticle creams, nail lacquer remover, etc. Hand sanitizers
Category 5D	0.09186352 %	Baby cream/lotion, baby oil, baby powders and talc
Category 6	0 %	Toothpaste Mouthwash, including breath sprays Toothpowder, strips, mouthwash tablets
Category 7A	0.53805774 %	Hair permanent or other hair chemical treatments (rinse-off) (e.g. relaxers), including rinse-off hair dyes
Category 7B	0.53805774 %	Hair sprays of all types (pumps, aerosol sprays, etc.) Hair styling aids non sprays (mousse, gels, leave- on conditioners) Hair permanent or other hair chemical treatments (leave-on) (e.g. relaxers), including leave-on hair dyes Shampoo - Dry (waterless shampoo) Hair deodorizer, hair perfume*
Category 8	0.09186352 %	Intimate wipes Intimate deodorant spray Tampons Baby wipes Toilet paper (wet)
Category 9	2.49343832 %	Bar soap Shampoo of all type Cleanser for face (rinse-off) Conditioner (rinse-off) Liquid soap Body washes and shower gels of all types Baby wash, bath, shampoo Bath gels, foams, mousses, salts, oils and other products



		added to bathwater (such as bath bombs) Foot care products (feet are placed in a bath for soaking) Shaving creams of all types (stick, gels, foams, etc.) All depilatories (including facial) and waxes for mechanical hair removal Shampoos for pets
Category 10A	2.49343832 %	Hand wash laundry detergent (including concentrates) Laundry pre-treatment of all types (e.g.paste, sprays, sticks) Hand dishwashing detergent (including concentrates) Hard surface cleaners of all types (bathroom and kitchen cleansers,furniture polish, etc.) Machine laundry detergents with skin contact (e.g. liquids, powders) including concentrates Toilet seat wipes Fabric softeners of all types excluding fabric softener sheets Household cleaning products, other types including fabric cleaners, soft surface cleaners, carpet cleaners, furniture polishes sprays and wipes, leather cleaning wipes, stain removers, fabric enhancing sprays, treatment products for textiles (e.g. starch sprays, fabric treated with fragrances after wash, deodorizers for textiles or fabrics) Floor wax Fragranced oil for lamp ring, reed diffusers, pot-pourri, liquid refills for air fresheners (non-cartridge systems), etc. Ironing water (Odorized distilled water) Dry cleaning kits (involving manual application on the textile)
Category 10B	15.7480315 %	Animal sprays – sprays applied to animals of all types Air freshener sprays, manual, including aerosol and pump Aerosol/spray insecticides
Category 11A	0.09186352 %	Feminine hygiene conventional pads,liners, interlabial pads Baby diapers Incontinence pant, pad Toilet paper (dry)
Category 11B	0.09186352 %	Tights with moisturizers Scented socks, gloves Facial tissues (dry tissues) Napkins Pillow spray Paper towels Wheat bags Facial masks (paper/protective) e.g.surgical masks not used as medical device Fertilizers, solid (pellet or powder)
Category 12	100 %	Candles of all types (including encased) Laundry detergents for machine wash with minimal skin contact (e.g. Liquid tabs, pods)



Automated air fresheners and fragrancing of all types (concentrated aerosol with metered doses (range 0.05-0.5mL/spray), plug-ins, closed systems, solid substrate, membrane delivery, electrical, powders, fragrancing sachets, incense, liquid refills (cartridge), air freshening crystals, solid non aerosol car diffuser)

Air delivery systems

Cat litter

Cell phone cases

Deodorizers/maskers not intended for skin contact (e.g. fabric drying machine deodorizers, carpet powders)

Dry cleaning kits (placed in the dryer)

Dryer sheets and fabric softener sheets

Fuels

Insecticides (e.g. mosquito coil, paper, electrical, for clothing) excluding aerosols/sprays

Joss sticks or incense sticks

Dishwash detergent and deodorizers – for machine wash

Olfactive board games

Paints

Plastic articles (excluding toys)

Scratch and sniff

Scent pack

Scent delivery system (using dry air technology)

Shoe polishes Rim blocks (toilet)

Toilet gel

Scent beads

For other kinds of application or use at higher concentration levels, a new evaluation may be needed; please contact: FRENCH COLOR & FRAGRANCE International.

Information about presence and concentration of fragrance ingredients subject to IFRA Standards in the fragrance mixture (SALTED CARAMEL #EU55145F) is as follows:

Materials under the scope of IFRA Standards	CAS-No.	Recommendat ion from IFRA Standard:	Concentration (%) in fragrance mixture or finished product	Comment
Toluene	108-88-3	Prohibited	0.0000525	
Anisyl alcohol	105-13-5 1331-81-3	Restricted	0.000525	
Citronellol	106-22-9 1117-61-9 141-25-3 26489-01-0 6812-78-8 68916-43-8 7540-51-4	Restricted	0.0000875	
Benzaldehyde	100-52-7	Restricted	0.3	
Cinnamic aldehyde	104-55-2	Restricted	7.5	
Benzyl benzoate	120-51-4	Restricted	76.2	

^{*}Actual use level or maximum use level



Phenylacetaldehyde	122-78-1	Restricted	0.1
Coumarin	91-64-5	Restricted	0.7
p-Methoxybenzaldehyde	123-11-5	Restricted	0.49
4-(4-Hydroxyphenyl)butan-2-one	5471-51-2	Restricted	0.45



Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878 Issue date: 5/3/2023 Revision date: 5/1/2025 Supersedes version of: 12/9/2024 Version: 2.1

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture

: SALTED CARAMEL #EU55145F Trade name

Product code : EU55145F

Type of product : Perfumes, fragrances Product group : Trade product

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

Main use category : Professional use, Industrial use

Industrial/Professional use spec : Industrial

For professional use only Use of the substance/mixture : Perfumes, fragrances Function or use category Odour agents

1.3. Details of the supplier of the safety data sheet

FRENCH COLOR & FRAGRANCE INTERNATIONAL GmbH GmbH

Mittlerer Weg 35 DE 79424 Auggen

Germany

T 49-7631-931-8900

SDS@frenchcolor.com, www.frenchcolor.com

1.4. Emergency telephone number

: 1-800-255-3924; +01-813-248-0585; China:+400-120-0751; Mexico:+01-800-099-0731; **Emergency number**

Brazil: +0-800-591-6042; India: +000-800-100-4086

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Acute toxicity (oral), Category 4 H302 Serious eye damage/eye irritation, Category 2 H319 H317 Skin sensitisation, Category 1 Hazardous to the aquatic environment - Acute Hazard, H400

Category 1

Hazardous to the aquatic environment - Chronic Hazard, H411

Category 2

Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

Harmful if swallowed. Causes serious eye irritation. Very toxic to aquatic life. Toxic to aquatic life with long lasting effects. May cause an allergic skin reaction.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)





GHS07

GHS09

Signal word (CLP) : Warning

Safety Data Sheet

Precautionary statements (CLP)

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Contains : Benzyl benzoate; Cinnamic aldehyde; 1,2-Cyclopentanedione, 3-methyl-; Veratryl aldehyde

(Veratraldehyde); COUMARIN; Phenylacetaldehyde

Hazard statements (CLP) : H302 - Harmful if swallowed.

H317 - May cause an allergic skin reaction.

H319 - Causes serious eye irritation.

H410 - Very toxic to aquatic life with long lasting effects.

: P261 - Avoid breathing dust/fume/gas/mist/vapours/spray.

P264 - Wash hands, forearms and face thoroughly after handling.

P270 - Do not eat, drink or smoke when using this product.

P272 - Contaminated work clothing should not be allowed out of the workplace.

P273 - Avoid release to the environment.

P280 - Wear protective gloves/protective clothing/eye protection/face protection/hearing

protection.

2.3. Other hazards

Contains no PBT and/or vPvB substances ≥ 0.1% assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
benzyl benzoate	CAS-No.: 120-51-4 EC-No.: 204-402-9 EC Index-No.: 607-085-00-9 REACH-no: 01-2119976371- 33	38.1 – 76.2	Acute Tox. 4 (Oral), H302 Aquatic Acute 1, H400 Aquatic Chronic 2, H411
Cinnamic aldehyde	CAS-No.: 104-55-2 EC-No.: 203-213-9 EC Index-No.: 606-155-00-6 REACH-no: 01-2119935242-	3.8 – 7.5	Acute Tox. 4 (Dermal), H312 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1A, H317 Aquatic Chronic 3, H412
Vanillin	CAS-No.: 121-33-5 EC-No.: 204-465-2 REACH-no: 01-2119516040-	1.40009 – 2.800175	Eye Irrit. 2, H319
Ethyl vanillin	CAS-No.: 121-32-4 EC-No.: 204-464-7 REACH-no: 01-211958961-24	1.314526 – 2.528245	Eye Irrit. 2, H319
1,2-Cyclopentanedione, 3-methyl-	CAS-No.: 765-70-8 EC-No.: 212-154-8	1 – 1.9	Acute Tox. 4 (Oral), H302 Skin Sens. 1, H317
COUMARIN	CAS-No.: 91-64-5 EC-No.: 202-086-7 REACH-no: 01-2119943756- 26	0.4 – 0.7	Acute Tox. 4 (Oral), H302 Skin Sens. 1B, H317
Veratryl aldehyde (Veratraldehyde)	CAS-No.: 120-14-9 EC-No.: 204-373-2	0.225 – 0.4375	Acute Tox. 4 (Oral), H302 Skin Sens. 1, H317

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
benzaldehyde substance with national workplace exposure limit(s) (BG, FI, HU, LT, LV, PL)	CAS-No.: 100-52-7 EC-No.: 202-860-4 EC Index-No.: 605-012-00-5 REACH-no: 01-2119455540-	0.2 – 0.3	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Repr. 2, H361 STOT SE 3, H335
1,2-Propanediol substance with national workplace exposure limit(s) (GB, HR, IE, LT, LV, PL, NO)	CAS-No.: 57-55-6 EC-No.: 200-338-0 REACH-no: 01-2119456809- 23	0.1 – 0.291	Not classified
isopentyl acetate substance with national workplace exposure limit(s) (AT, BE, BG, CY, DE, DK, EE, ES, FI, FR, GI, GR, HR, HU, IE, IT, LT, LU, LV, MT, NL, PL, PT, RO, SE, SI, SK, NO, CH, TR); substance with a Community workplace exposure limit	CAS-No.: 123-92-2 EC-No.: 204-662-3 EC Index-No.: 607-130-00-2 REACH-no: 01-2119548408- 32	0.1 – 0.15	Flam. Liq. 3, H226
Phenylacetaldehyde	CAS-No.: 122-78-1 EC-No.: 204-574-5 REACH-no: 01-2120766865- 37	0.1 – 0.1	Acute Tox. 4 (Oral), H302 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1B, H317 Aquatic Chronic 3, H412
Dipropylene glycol monomethyl ether substance with national workplace exposure limit(s) (AT, BE, BG, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GI, GR, HR, HU, IE, IT, LT, LU, LV, MT, NL, PL, PT, RO, SE, SI, SK, NO, CH, TR); substance with a Community workplace exposure limit	CAS-No.: 34590-94-8 EC-No.: 252-104-2	0.002286 – 0.004445	Not classified
Toluene substance with national workplace exposure limit(s) (AT, BE, BG, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GI, GR, HR, HU, IE, IT, LT, LU, LV, MT, NL, PL, PT, RO, SE, SI, SK, NO, CH, TR); substance with a Community workplace exposure limit	CAS-No.: 108-88-3 EC-No.: 203-625-9 EC Index-No.: 601-021-00-3	≤ 0.0000525	Not classified

Specific concentration limits:			
Name	Product identifier	Specific concentration limits (%)	
Cinnamic aldehyde	EC-No.: 203-213-9	(0.001 < C < 0.01) EUH208 (0.01 ≤ C < 0.1) Skin Sens. 1; H317 (0.1 ≤ C < 100) Skin Sens. 1A; H317	

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general

: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible). Call a poison center or a doctor if you feel unwell.

First-aid measures after inhalation

: Remove person to fresh air and keep comfortable for breathing. Allow affected person to

breathe fresh air. Allow the victim to rest.

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

First-aid measures after skin contact : Remove affected clothing and wash all exposed skin area with mild soap and water,

followed by warm water rinse. If skin irritation or rash occurs: Get medical advice/attention. Specific treatment (see Get medical advice/attention. on this label). If skin irritation occurs: Get medical advice/attention. Wash with plenty of water/.... Get medical advice/attention. Wash contaminated clothing before reuse. Wash skin with plenty of water. Take off

contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.

First-aid measures after eye contact

If eye irritation persists: Get medical advice/attention. Rinse immediately with plenty of

water. Obtain medical attention if pain, blinking or redness persists. Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue

rinsing. If eye irritation persists: Get medical advice/attention.

First-aid measures after ingestion : Do NOT induce vomiting. Obtain emergency medical attention. Call a POISON

CENTER/doctor if you feel unwell. Rinse mouth. Call a poison center or a doctor if you feel

unwell.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects : Not expected to present a significant hazard under anticipated conditions of normal use.

Symptoms/effects after skin contact : May cause an allergic skin reaction.

Symptoms/effects after eye contact : Causes serious eye irritation. Eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Sand. Water spray. Dry powder. Foam. Carbon dioxide.

Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.3. Advice for firefighters

Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any

chemical fire. Prevent fire fighting water from entering the environment.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

Do not attempt to take action without suitable protective equipment. Self-contained

breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Emergency procedures : Ventilate spillage area. Evacuate unnecessary personnel. Avoid contact with skin and eyes.

Avoid breathing dust/fume/gas/mist/vapours/spray.

For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. Equip cleanup crew

with proper protection. For further information refer to section 8: "Exposure

controls/personal protection".

Emergency procedures : Ventilate area.

6.2. Environmental precautions

Avoid release to the environment. Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

For containment : Collect spillage.

5/1/2025 (Revision date) EN (English) 4/33

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Methods for cleaning up : Take up liquid spill into absorbent material. Soak up spills with inert solids, such as clay or

diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.

Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

See Section 8. Exposure controls and personal protection. For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Wash hands and other exposed areas with mild

soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapour. Avoid contact with skin and eyes. Wear personal protective equipment. Avoid breathing dust/fume/gas/mist/vapours/spray.

Hygiene measures : Wash hands thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Do not eat, drink or smoke

when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep only in the original container in a cool, well ventilated place away from : Keep away

from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container closed when not in use. Store in a well-ventilated place. Keep cool.

Incompatible products : Strong bases. Strong acids.

Incompatible materials : Sources of ignition. Direct sunlight.

Storage temperature : 25 °C

Storage area : Store in a well-ventilated place. Store away from heat.

Special rules on packaging : Store in a closed container.

Packaging materials : Do not store in corrodable metal.

Germany

Storage class (LGK, TRGS 510) : LGK 10 - Combustible liquids

Joint storage table : LGK 1 LGK 2A LGK 2B LGK 3

•	LGK 1	LGK 2A	LGK 2B	LGK 3	LGK 4.1A
	LGK 4.1B	LGK 4.2	LGK 4.3	LGK 5.1A	LGK 5.1B
	LGK 5.1C	LGK 5.2	LGK 6.1A	LGK 6.1B	LGK 6.1C
	LGK 6.1D	LGK 6.2	LGK 7	LGK 8A	LGK 8B
	LGK 10	LGK 11	LGK 12	LGK 13	LGK 10-13

Joint storage not permitted for : LGK 1, LGK 2A, LGK 5.1A, LGK 6.2, LGK 7

Joint storage with restrictions permitted for : LGK 4.1A, LGK 4.2, LGK 4.3, LGK 5.1B, LGK 5.1C, LGK 5.2

Joint storage permitted for : LGK 2B, LGK 3, LGK 4.1B, LGK 6.1A, LGK 6.1B, LGK 6.1C, LGK 6.1D, LGK 8A, LGK 8B,

LGK 10, LGK 11, LGK 12, LGK 13, LGK 10-13

Switzerland

Storage class (LK) : LK 10/12 - Liquids

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

National occupational exposure and biological limit values

Toluene (108-88-3)	
EU - Indicative Occupational Exposure Limit (IOEL)	
IOEL TWA	192 mg/m³

5/1/2025 (Revision date) EN (English) 5/33

Safety Data Sheet

Toluene (108-88-3)	
	50 ppm
IOEL STEL	384 mg/m³
	100 ppm
Remark	Possibility of significant uptake through the skin
Austria - Occupational Exposure Limits	
MAK (OEL TWA)	190 mg/m³
	50 ppm
MAK (OEL STEL)	380 mg/m³
	100 ppm
OEL chemical category	Skin notation
Belgium - Occupational Exposure Limit	S
OEL TWA	77 mg/m³
	20 ppm
OEL STEL	384 mg/m³
	100 ppm
OEL chemical category	Skin, Skin notation
Bulgaria - Occupational Exposure Limit	S
OEL TWA	192 mg/m³
	50 ppm
OEL STEL	384 mg/m³
	100 ppm
Bulgaria - Biological limit values	
BLV	1.6 mmol/mmol Creatinine Parameter: Hippuric acid - Medium: urine - Sampling time: at the end of exposure or end of work shift
Croatia - Occupational Exposure Limits	
GVI (OEL TWA)	192 mg/m³
	50 ppm
KGVI (OEL STEL)	384 mg/m³
	100 ppm
OEL chemical category	Skin notation
Croatia - Biological limit values	
1 mg/l Parameter: Toluene - Medium: blood - Sampling time: at the end of the work shift 20 ppm Parameter: Toluene - Medium: final exhaled air - Sampling time: during exposu 2.5 g/g creatinine Parameter: Hippuric acid - Medium: urine - Sampling time: at the end the work shift (calculated on the average Creatinine value of 1.2 g/L urine) 1 mg/g creatinine Parameter: o-Cresol - Medium: urine - Sampling time: at the end of the work shift (calculated on the average Creatinine value of 1.2 g/L urine)	
Cyprus - Occupational Exposure Limits	
OEL TWA	192 mg/m³
	50 ppm
OEL STEL	384 mg/m³

Safety Data Sheet

Toluene (108-88-3)		
	100 ppm	
OEL chemical category	Skin-potential for cutaneous absorption	
Czech Republic - Occupational Exposure Limits		
PEL (OEL TWA)	200 mg/m³	
OEL chemical category	Potential for cutaneous absorption	
Czech Republic - Biological limit values		
BLV	1.6 µmol/mmol Creatinine Parameter: o-Cresol - Medium: urine - Sampling time: end of shift (after hydrolysis) 1000 µmol/mmol Creatinine Parameter: Hippuric acid - Medium: urine - Sampling time: end of shift (exposure testing using the o-Cresol parameter to precisely measure Toluene exposure is needed if the value of Hippuric acid is between 1600 and 2500 mg/g of Creatinine, no additional testing is needed if the Hippuric acid value is >2500 mg/g of Creatinine as work exposure to Toluene will have highly exceeded the PEL value.) 1.5 mg/g creatinine Parameter: o-Cresol - Medium: urine - Sampling time: end of shift (after hydrolysis) 1600 mg/g creatinine Parameter: Hippuric acid - Medium: urine - Sampling time: end of shift (exposure testing using the o-Cresol parameter to precisely measure Toluene exposure is needed if the value of Hippuric acid is between 1600 and 2500 mg/g of Creatinine, no additional testing is needed if the Hippuric acid value is >2500 mg/g of Creatinine as work exposure to Toluene will have highly exceeded the PEL value.)	
Denmark - Occupational Exposure Limits		
OEL TWA	94 mg/m³	
	25 ppm	
OEL STEL	384 mg/m³	
	100 ppm	
OEL chemical category	Potential for cutaneous absorption	
Estonia - Occupational Exposure Limits		
OEL TWA	192 mg/m³	
	50 ppm	
OEL STEL	384 mg/m³	
	100 ppm	
OEL chemical category	Skin notation	
Finland - Occupational Exposure Limits		
HTP (OEL TWA)	81 mg/m³	
	25 ppm	
HTP (OEL STEL)	380 mg/m³	
	100 ppm	
OEL chemical category	Potential for cutaneous absorption	
Finland - Biological limit values		
BLV	500 nmol/L Parameter: Toluene - Medium: blood - Sampling time: in the morning after a working day	
France - Occupational Exposure Limits		
VME (OEL TWA)	76.8 mg/m³ (restrictive limit)	
	20 ppm (restrictive limit)	

Safety Data Sheet

Toluene (108-88-3)		
VLE (OEL C/STEL)	384 mg/m³ (restrictive limit)	
	100 ppm (restrictive limit)	
OEL chemical category	Reproductive Toxin category 2, Risk of cutaneous absorption	
France - Biological limit values		
BLV	20 μg/l Parameter: Toluene - Medium: blood - Sampling time: end of workweek (Semi-quantitative (ambiguous interpretation)) Parameter: Hippuric acid - Medium: urine - Sampling time: end of shift (per the Authority, the values for this substance must be decided and/or determined on a case by case basis. Guidance for the calculation of and interpretation of values is provided in the source)	
Germany - Occupational Exposure Limits (TRGS 9	00)	
AGW (OEL TWA)	190 mg/m³ (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)	
	50 ppm (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)	
Chemical category	Skin notation	
Germany - Biological limit values (TRGS 903)		
Biological limit value	600 µg/l Parameter: Toluene - Medium: whole blood - Sampling time: immediately after exposure 75 µg/l Parameter: Toluene - Medium: urine - Sampling time: end of exposure or shift 1.5 mg/l Parameter: o-Cresol (after hydrolysis) - Medium: urine - Sampling time: at the end of the shift, in case of long-term exposure after several previous shifts	
Gibraltar - Occupational Exposure Limits		
OEL TWA	192 mg/m³	
	50 ppm	
OEL STEL	384 mg/m³	
	100 ppm	
OEL chemical category	Skin notation	
Greece - Occupational Exposure Limits		
OEL TWA	192 mg/m³	
	50 ppm	
OEL STEL	384 mg/m³	
	100 ppm	
OEL chemical category	skin - potential for cutaneous absorption	
Hungary - Occupational Exposure Limits	•	
AK (OEL TWA)	190 mg/m³	
CK (OEL STEL)	384 mg/m³	
OEL chemical category	Potential for cutaneous absorption	
Ireland - Occupational Exposure Limits		
OEL TWA	192 mg/m³	
	50 ppm	
OEL STEL	384 mg/m³	
	100 ppm	

Safety Data Sheet

Toluene (108-88-3)		
OEL chemical category	Potential for cutaneous absorption	
Italy - Occupational Exposure Limits		
OEL TWA	192 mg/m³	
	50 ppm	
OEL chemical category	skin - potential for cutaneous absorption	
Latvia - Occupational Exposure Limits		
OEL TWA	50 mg/m³	
	14 ppm	
OEL chemical category	skin - potential for cutaneous exposure	
Latvia - Biological Exposure Indices		
BEI	600 μg/l Parameter: Toluene - Medium: blood - Sampling time: at the end of exposure (for assessment of long-term exposure, samples are taken at the end of a shift after several previous shifts) 75 μg/l Parameter: Toluene - Medium: urine - Sampling time: end of shift (for assessment of long-term exposure, samples are taken at the end of a shift after several previous shifts) 1.5 mg/l Parameter: o-Cresol - Medium: urine - Sampling time: at the end of exposure or shift (after hydrolysis)	
Lithuania - Occupational Exposure Limits		
IPRV (OEL TWA)	192 mg/m³	
	50 ppm	
TPRV (OEL STEL)	384 mg/m³	
	100 ppm	
OEL chemical category	Reproductive toxin, Skin notation	
Luxembourg - Occupational Exposure Limits		
OEL TWA	192 mg/m³	
	50 ppm	
OEL STEL	384 mg/m³	
	100 ppm	
OEL chemical category	Possibility of significant uptake through the skin	
Malta - Occupational Exposure Limits		
OEL TWA	192 mg/m³	
	50 ppm	
OEL STEL	384 mg/m³	
	100 ppm	
OEL chemical category	Possibility of significant uptake through the skin	
Netherlands - Occupational Exposure Limits		
TGG-8u (OEL TWA)	150 mg/m³	
	39 ppm	
TGG-15min (OEL STEL)	384 mg/m³	
	100 ppm	
	I	

Safety Data Sheet

Toluene (108-88-3)	
Poland - Occupational Exposure Limits	
NDS (OEL TWA)	100 mg/m³
NDSCh (OEL STEL)	200 mg/m³
Portugal - Occupational Exposure Limits	
OEL TWA	192 mg/m³ (indicative limit value)
	50 ppm (indicative limit value)
OEL STEL	384 mg/m³ (indicative limit value)
	100 ppm (indicative limit value)
OEL chemical category	A4 - Not Classifiable as a Human Carcinogen, skin - potential for cutaneous exposure indicative limit value
Romania - Occupational Exposure Limits	
OEL TWA	192 mg/m³
	50 ppm
OEL STEL	384 mg/m³
	100 ppm
OEL chemical category	Skin notation
Romania - Biological limit values	
BLV	2 g/l Parameter: Hippuric acid - Medium: urine - Sampling time: end of shift 3 mg/l Parameter: o-Cresol - Medium: urine - Sampling time: end of shift
Slovakia - Occupational Exposure Limits	
NPHV (OEL TWA)	192 mg/m³
	50 ppm
NPHV (OEL C)	384 mg/m³ (also biological monitoring considered)
OEL chemical category	Potential for cutaneous absorption
Slovakia - Biological limit values	
BLV	600 µg/l Parameter: Toluene - Medium: blood - Sampling time: end of exposure or work shift 1.5 mg/l Parameter: o-Cresol - Medium: urine - Sampling time: after all work shifts (for long-term exposure) 1.5 mg/l Parameter: o-Cresol - Medium: urine - Sampling time: end of exposure or work shift 2401 mg/g creatinine Parameter: Hippuric acid - Sampling time: end of exposure or work shift
Slovenia - Occupational Exposure Limits	
OEL TWA	192 mg/m³
	50 ppm
OEL STEL	384 mg/m³
	100 ppm
OEL chemical category	Category 2, Potential for cutaneous absorption
Spain - Occupational Exposure Limits	
VLA-ED (OEL TWA)	192 mg/m³ (indicative limit value)
	50 ppm (indicative limit value)

Safety Data Sheet

Toluene (108-88-3)		
VLA-EC (OEL STEL)	384 mg/m³	
	100 ppm	
OEL chemical category	skin - potential for cutaneous absorption	
Spain - Biological limit values		
BLV	0.6 mg/l Parameter: o-Cresol - Medium: urine - Sampling time: end of shift 0.05 mg/l Parameter: Toluene - Medium: blood - Sampling time: start of last shift of workweek 0.08 mg/l Parameter: Toluene - Medium: urine - Sampling time: end of shift	
Sweden - Occupational Exposure Limits		
NGV (OEL TWA)	192 mg/m³	
	50 ppm	
KGV (OEL STEL)	384 mg/m³	
	100 ppm	
OEL chemical category	Skin notation	
United Kingdom - Occupational Exposure Limits		
WEL TWA (OEL TWA)	191 mg/m³	
	50 ppm	
WEL STEL (OEL STEL)	384 mg/m³	
	100 ppm	
WEL chemical category	Potential for cutaneous absorption	
Norway - Occupational Exposure Limits		
Grenseverdi (OEL TWA)	94 mg/m³	
	25 ppm	
Korttidsverdi (OEL STEL)	141 mg/m³ (value calculated)	
	37.5 ppm (value calculated)	
OEL chemical category	Skin notation	
Switzerland - Occupational Exposure Limits		
MAK (OEL TWA)	190 mg/m³	
	50 ppm	
KZGW (OEL STEL)	760 mg/m³	
	200 ppm	
OEL chemical category	Skin notation, Category 2 reproductive toxin	

Safety Data Sheet

Toluene (108-88-3)	
Switzerland - BAT	
BAT	600 μg/l Parameter: Toluene - Medium: whole blood - Sampling time: end of shift 6.48 μmol/l Parameter: Toluene - Medium: whole blood - Sampling time: end of shift 2 g/g creatinine Parameter: Hippuric acid - Medium: urine - Sampling time: end of shift, and after several shifts (for long-term exposures) Parameter: Hippuric acid - Medium: urine - Sampling time: end of shift, and after several shifts (for long-term exposures) 0.5 mg/l Parameter: o-Cresol - Medium: urine - Sampling time: end of shift, and after several shifts (for long-term exposures) 4.62 μmol/l Parameter: o-Cresol - Medium: urine - Sampling time: end of shift, and after several shifts (for long-term exposures) 75 μg/l Parameter: Toluol - Medium: urine - Sampling time: end of shift
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL TWA	20 ppm
ACGIH chemical category	Not Classifiable as a Human Carcinogen
USA - ACGIH - Biological Exposure Indices	
BEI	0.02 mg/l Parameter: Toluene - Medium: blood - Sampling time: prior to last shift of workweek 0.03 mg/l Parameter: Toluene - Medium: urine - Sampling time: end of shift 0.3 mg/g creatinine Parameter: o-Cresol with hydrolysis - Medium: urine - Sampling time: end of shift (background)
Dipropylene glycol monomethyl ether (34590-	94-8)
EU - Indicative Occupational Exposure Limit (IOEL)	
IOEL TWA	308 mg/m³
	50 ppm
Remark	Possibility of significant uptake through the skin
Austria - Occupational Exposure Limits	
MAK (OEL TWA)	307 mg/m³ (mixed isomers)
	50 ppm (mixed isomers)
MAK (OEL STEL)	614 mg/m³ (isomers mixtures)
	100 ppm (isomers mixtures)
OEL chemical category	Skin notation
Belgium - Occupational Exposure Limits	
OEL TWA	308 mg/m³
	50 ppm
OEL chemical category	Skin, Skin notation
Bulgaria - Occupational Exposure Limits	
OEL TWA	308 mg/m³
	50 ppm
Croatia - Occupational Exposure Limits	
GVI (OEL TWA)	308 mg/m³
	50 ppm
OEL chemical category	Skin notation

Safety Data Sheet

Cyprus - Occupational Exposure Limits 308 mg/m² OEL TWA 308 mg/m² OEL chemical category \$kin-potential for cutaneous absorption Czech Republic - Occupational Exposure Limits 270 mg/m² OEL Chemical category Potential for cutaneous absorption OEL Chemical Category Potential for cutaneous absorption OEL TWA 309 mg/m² 500 ppm 618 mg/m² 610 ppm 618 mg/m² OEL Chemical category Potential for cutaneous absorption Estonia - Occupational Exposure Limits 60 ppm OEL TWA 308 mg/m² OEL Chemical category \$kin notation OEL Chemical category \$to ppm OEL Chemical category potential for cutaneous absorption Prance - Occupational Exposure Limits \$to ppm OEL Chemical category potential for cutaneous absorption OEL Chemical category \$to ppm (restrictive limit) OEL Chemical category \$to ppm (restrictive limit) <th colspan="2">Dipropylene glycol monomethyl ether (34590-94-8)</th>	Dipropylene glycol monomethyl ether (34590-94-8)		
OFE Depm OFE Depm OFE Depm Czech Republic - Occupational Exposure Limits 270 mg/m² OFE Depm OFE Depm Denmark - Occupational Exposure Limits 309 mg/m² SD pm 500 ppm OFE B18 mg/m² 100 ppm 100 ppm OFE Potential for cutaneous absorption Eatonia - Occupational Exposure Limits 100 ppm OFE 308 mg/m² 50 ppm 308 mg/m² 50 ppm 309 mg/m² OFE 300 ppm OFE 400 ppm	Cyprus - Occupational Exposure Limits		
OEL chemical category Skin-potential for cutaneous absorption Czech Republic - Occupational Exposure Limits PEL (DEL TWA) 270 mg/m² OEL chemical category Potential for cutaneous absorption Demanark - Occupational Exposure Limits OEL TWA 309 mg/m² 60 ppm OEL chemical category Potential for cutaneous absorption Eatonia - Occupational Exposure Limits OEL TWA 308 mg/m³ OEL chemical category Skin cotation Finland - Occupational Exposure Limits VME (OEL TWA) 308 mg/m² (restrictive limit) Open (restrictive limit) OCL chemical category Risk of outaneous absorption Gibraliar - Occupational Exposure Limits (TRGS 900 mg/m² (restrictive limit) OEL TWA 308 mg/m² (restrictive limit) OEL TWA <td>OEL TWA</td> <td>308 mg/m³</td>	OEL TWA	308 mg/m³	
Czech Republic - Occupational Exposure Limits PEL (DEL TWA) 270 mg/m³ OEL chemical category Potential for cutaneous absorption Denmark - Occupational Exposure Limits OEL TWA 309 mg/m³ 50 ppm 618 mg/m³ 100 ppm 100 ppm OEL Affect 618 mg/m³ 100 ppm Potential for cutaneous absorption Estonia - Occupational Exposure Limits 308 mg/m³ OEL TWA 308 mg/m³ OEL chemical category 50 ppm OEL chemical category 50 ppm OEL chemical category 310 mg/m³ Finance - Occupational Exposure Limits 50 ppm OEL chemical category 70 ppm (restrictive limit) OEL chemical category 808 mg/m³ (restrictive limit) OEL chemical category 810 mg/m³ (somer mixture) Gibraltar - Occupational Exposure Limits 50 ppm (somer mixture) Gibraltar - Occupational Exposure Limits 50 ppm (somer mixture) Gibraltar - Occupational Exposure Limits 50 ppm (somer mixture) OEL TWA 308 mg/m³ </td <td></td> <td>50 ppm</td>		50 ppm	
PEL (OEL TWA) 270 mg/m² OEL chemical category Potential for cutaneous absorption Denmark - Occupational Exposure Limits OEL TWA 309 mg/m² 50 ppm 100 ppm OEL STEL 618 mg/m² 100 ppm 100 ppm DEL chemical category Potential for cutaneous absorption Estonia - Occupational Exposure Limits OEL TWA 308 mg/m² 50 ppm 50 ppm OEL chemical category Potential for cutaneous absorption Finance - Occupational Exposure Limits VME (OEL TWA) 308 mg/m² (restrictive limit) OEL chemical category Risk of cutaneous absorption OEL chemical category Risk of cutaneous absorption Germany - Occupational Exposure Limits (TRCS 900**) OEL chemical category Risk of cutaneous absorption Gibratar - Occupational Exposure Limits OEL TWA 308 mg/m² (somer mixture) 50 ppm 50 ppm (somer mixture) 60 ppm 50 ppm <td colspa<="" td=""><td>OEL chemical category</td><td>Skin-potential for cutaneous absorption</td></td>	<td>OEL chemical category</td> <td>Skin-potential for cutaneous absorption</td>	OEL chemical category	Skin-potential for cutaneous absorption
Denmark - Occupational Exposure Limits 309 mg/m² 50 pm 50 pm QEL STEL 80 pm QEL STEL 100 ppm QEL chemical category Potential for cutaneous absorption ESTONIA - Occupational Exposure Limits 308 mg/m³ 50 ppm 50 ppm QEL TWA 308 mg/m³ 50 ppm 50 ppm QEL Chemical category 8 kin notation FINIAN - Occupational Exposure Limits 310 mg/m³ FORD - Occupational Exposure Limits 50 ppm FARCE - Occupational Exposure Limits 90 pm VME (OEL TWA) 308 mg/m³ (restrictive limit) 50 ppm (restrictive limit) 50 ppm (restrictive limit) 60 Cut chemical category 8 kof cutaneous absorption Germany - Occupational Exposure Limits (TRGS SW) 50 ppm (restrictive limit) 60 ppm (somer mixture) 50 ppm (somer mixture) 60 ppm (somer mixture) 50 ppm (somer mixture) 61 ppm (somer mixture) 50 ppm 62 ppm (somer mixture) 50 ppm 63 ppm 50 ppm	Czech Republic - Occupational Exposure Limits		
Demant - Occupational Exposure Limits OEL TWA 309 mg/m³ 50 ppm 618 mg/m³ 100 ppm 100 ppm OEL STEL 618 mg/m³ 0EL chemical category Potential for cutaneous absorption Estonia - Occupational Exposure Limits FINITIAN 308 mg/m³ 50 ppm OEL chemical category Skin notation Finitiand - Occupational Exposure Limits Finitiand - Occupational Exposure Limits Finitiand - Occupational Exposure Limits VIME (OEL TWA) 308 mg/m³ 50 ppm (restrictive limit) OEL chemical category Risk of cutaneous absorption Germany - Occupational Exposure Limits (TRGS) Gibraltar - Occupational Exposure Limits (TRGS) Gibraltar - Occupational Exposure Limits OEL TWA 308 mg/m³	PEL (OEL TWA)	270 mg/m³	
OEL TWA 309 mg/m³ 50 ppm OEL STEL 618 mg/m³ 100 ppm 100 ppm OEL chemical category Potential for cutaneous absorption ESTONIA - Occupational Exposure Limits 308 mg/m³ 50 ppm 50 ppm OEL chemical category \$kin notation FINITIAN - Occupational Exposure Limits 310 mg/m³ 50 ppm 50 ppm OEL chemical category Potential for cutaneous absorption FRANCE - Occupational Exposure Limits 308 mg/m³ (restrictive limit) OEL chemical category Risk of cutaneous absorption Germany - Occupational Exposure Limits (TRGS) Trace - Occupational Exposure Limits (TRGS) GEL TWA) 310 mg/m² (somer mixture) Gibraltar - Occupational Exposure Limits (TRGS) 50 ppm (somer mixture) Gibraltar - Occupational Exposure Limits 50 ppm (somer mixture) Gibraltar - Occupational Exposure Limits 50 ppm (somer mixture) Gibraltar - Occupational Exposure Limits 50 ppm (somer mixture) Gibraltar - Occupational Exposure Limits 50 ppm (somer mixture) OEL Chemica	OEL chemical category	Potential for cutaneous absorption	
Potential Category 50 ppm OEL Chemical category Potential for cutaneous absorption Estonia - Occupational Exposure Limits 308 mg/m³ OEL TWA 308 mg/m³ OEL chemical category Skin notation Finland - Occupational Exposure Limits 310 mg/m³ Finland - Occupational Exposure Limits 50 ppm OEL chemical category Potential for cutaneous absorption France - Occupational Exposure Limits 50 ppm OEL chemical category Potential for cutaneous absorption France - Occupational Exposure Limits 50 ppm (restrictive limit) OEL chemical category Risk of cutaneous absorption Germany - Occupational Exposure Limits (TROS) 50 ppm (restrictive limit) OEL TWA) 310 mg/m³ (isomer mixture) 50 ppm (isomer mixture) 50 ppm (isomer mixture) 60 ppm 50 ppm OEL TWA 308 mg/m³ 50 ppm 50 ppm OEL chemical category 50 ppm OEL chemical category 50 ppm OEL themical category 50 ppm	Denmark - Occupational Exposure Limits		
OEL STEL 618 mg/m³ OEL chemical category Potential for cutaneous absorption Estonia - Occupational Exposure Limits OEL TWA 308 mg/m³ 50 ppm 50 ppm OEL chemical category Skin notation Finland - Occupational Exposure Limits HTP (OEL TWA) 310 mg/m³ 50 ppm Poential for cutaneous absorption France - Occupational Exposure Limits VME (OEL TWA) 308 mg/m³ (restrictive limit) 50 ppm (restrictive limit) 50 ppm (restrictive limit) OCL chemical category Risk of cutaneous absorption Germany - Occupational Exposure Limits (TRGS 900**) AGW (OEL TWA) 310 mg/m³ (isomer mixture) 50 ppm (isomer mixture) Gibraltar - Occupational Exposure Limits (TRGS 900**) OEL TWA 308 mg/m³ 50 ppm 50 ppm OEL chemical category Skin notation Gibraltar - Occupational Exposure Limits OEL TWA 50 ppm OEL Chemical category	OEL TWA	309 mg/m³	
New Protection of State (1997) Potential for cutaneous absorption Estonia - Occupational Exposure Limits OEL TWA 308 mg/m³ 50 ppm Skin notation Finand - Occupational Exposure Limits HTP (OEL TWA) 310 mg/m³ 50 ppm Potential for cutaneous absorption France - Occupational Exposure Limits YME (OEL TWA) 308 mg/m³ (restrictive limit) 50 ppm (restrictive limit) 50 ppm (restrictive limit) OEL chemical category Risk of cutaneous absorption Germany - Occupational Exposure Limits (TRGS 900**) AGW (OEL TWA) 310 mg/m³ (somer mixture) 60 ppm (somer mixture) 50 ppm (somer mixture) 60 ppm (somer mixture) 50 ppm Gibraltar - Occupational Exposure Limits OEL themical category 308 mg/m³ OEL themical category \$kin notation Gibraltar - Occupational Exposure Limits OEL themical category \$kin notation OEL themical category \$kin notation OEL TW		50 ppm	
OEL chemical category Potential for cutaneous absorption Estonia - Occupational Exposure Limits OEL TWA 308 mg/m³ 50 ppm OEL chemical category 8kin notation Finand - Occupational Exposure Limits HTP (OEL TWA) 310 mg/m³ 50 ppm 900 OEL chemical category Potential for cutaneous absorption France - Occupational Exposure Limits WME (OEL TWA) 308 mg/m³ (restrictive limit) 50 ppm (restrictive limit) 50 ppm (restrictive limit) 6CH Chemical category Risk of cutaneous absorption Germany - Occupational Exposure Limits (TRGS 900) 310 mg/m³ (isomer mixture) 50 ppm (isomer mixture) 50 ppm (isomer mixture) 50 ppm (isomer mixture) 50 ppm (isomer mixture) 60 ppm (isomer mixture) 60 ppm (isomer mixture) 60 ppm (isomer mixture) 60 ppm (isomer mixture) 60 ppm (isomer mixture)	OEL STEL	618 mg/m³	
Estonia - Occupational Exposure Limits OEL TWA 308 mg/m³ 50 ppm 50 ppm OEL chemical category \$kin notation Finland - Occupational Exposure Limits 310 mg/m³ HTP (OEL TWA) 310 mg/m³ 0EL chemical category Potential for cutaneous absorption France - Occupational Exposure Limits VME (OEL TWA) 308 mg/m³ (restrictive limit) 50 ppm (restrictive limit) 50 ppm (restrictive limit) OEL chemical category Risk of cutaneous absorption Germany - Occupational Exposure Limits (TRGS 90") AGW (OEL TWA) 310 mg/m³ (somer mixture) GIbraltar - Occupational Exposure Limits 308 mg/m³ (somer mixture) 50 ppm (isomer mixture) GEL TWA 308 mg/m³ (somer mixture) 50 ppm OEL chemical category 8 kin notation Greece - Occupational Exposure Limits 600 mg/m³ (somer mixture) OEL TWA 600 mg/m³ (somer mixture) OEL TWA 50 ppm		100 ppm	
OEL TWA 308 mg/m³ OEL chemical category 5kin notation FINITIAN - Occupational Exposure Limits 310 mg/m³ DEL chemical category Potential for cutaneous absorption France - Occupational Exposure Limits 308 mg/m³ (restrictive limit) VME (OEL TWA) 308 mg/m³ (restrictive limit) OEL chemical category Risk of cutaneous absorption Germany - Occupational Exposure Limits (TRGS 900 mg/m² (isomer mixture) 310 mg/m² (isomer mixture) GIbraltar - Occupational Exposure Limits 308 mg/m³ (isomer mixture) GIL TWA 308 mg/m³ (isomer mixture) OEL Chemical category 308 mg/m³ (isomer mixture) OEL TWA 308 mg/m³ (isomer mixture) OEL Chemical category 300 mg/m³ (isomer mixture) OEL TWA 600 mg/m³ (isomer mixture) OEL T	OEL chemical category	Potential for cutaneous absorption	
So ppm	Estonia - Occupational Exposure Limits		
OEL chemical category Skin notation Finand - Occupational Exposure Limits HTP (OEL TWA) 310 mg/m³ 50 ppm OEL chemical category Potential for cutaneous absorption France - Occupational Exposure Limits WE (OEL TWA) 308 mg/m³ (restrictive limit) OEL chemical category Risk of cutaneous absorption Germany - Occupational Exposure Limits (TRGS 90") AGW (OEL TWA) 310 mg/m³ (isomer mixture) 60 ppm (isomer mixture) 50 ppm (isomer mixture) 60 ppm (isomer mixture) OEL TWA 308 mg/m³ 50 ppm OEL chemical category Skin notation Greece - Occupational Exposure Limits OEL TWA 600 mg/m³ 600 mg/m³ 100 ppm OEL TWA 600 mg/m³ 600 mg/m³ 100 ppm	OEL TWA	308 mg/m³	
Finand - Occupational Exposure Limits HTP (OEL TWA) 310 mg/m³ 50 ppm OEL chemical category Potential for cutaneous absorption France - Occupational Exposure Limits WME (OEL TWA) 308 mg/m³ (restrictive limit) 50 ppm (restrictive limit) 00L chemical category Risk of cutaneous absorption Germany - Occupational Exposure Limits (TRGS 900- AGW (OEL TWA) 310 mg/m³ (isomer mixture) 50 ppm (isomer mixture) Gibraltar - Occupational Exposure Limits OEL TWA 308 mg/m³ 50 ppm OEL chemical category Skin notation Greece - Occupational Exposure Limits OEL TWA 600 mg/m³ 100 ppm OEL TWA 600 mg/m³ 100 ppm OEL STEL 600 mg/m³ 100 ppm		50 ppm	
HTP (OEL TWA) 310 mg/m³ 50 ppm OEL chemical category Potential for cutaneous absorption France - Occupational Exposure Limits WME (OEL TWA) 308 mg/m³ (restrictive limit) 50 ppm (restrictive limit) COEL chemical category Risk of cutaneous absorption Germany - Occupational Exposure Limits (TRGS) AGW (OEL TWA) 310 mg/m³ (isomer mixture) 50 ppm (isomer mixture) 50 ppm (isomer mixture) Gibraltar - Occupational Exposure Limits OEL TWA 308 mg/m³ 50 ppm OEL chemical category Skin notation Greece - Occupational Exposure Limits OEL TWA 600 mg/m³ 100 ppm OEL TWA 100 ppm DEL TWA 100 ppm DEL TWA 100 ppm 100 ppm 100 ppm 100 ppm	OEL chemical category	Skin notation	
DEL chemical category Potential for cutaneous absorption France - Occupational Exposure Limits VME (OEL TWA) 308 mg/m³ (restrictive limit) 50 ppm (restrictive limit) 50 ppm (restrictive limit) 60 ppm (restrictive limit) OEL chemical category Risk of cutaneous absorption Germany - Occupational Exposure Limits (TRGS 900) AGW (OEL TWA) 310 mg/m³ (isomer mixture) 50 ppm (isomer mixture) 60 ppm (isomer mixture) 61 ppm OEL TWA 308 mg/m³ 50 ppm OEL chemical category Skin notation Greece - Occupational Exposure Limits Greece - Occupational Exposure Limits OEL TWA 600 mg/m³ 100 ppm OEL STEL OEL STEL 900 mg/m³ 150 ppm	Finland - Occupational Exposure Limits		
OEL chemical category Potential for cutaneous absorption France - Occupational Exposure Limits VME (OEL TWA) 308 mg/m³ (restrictive limit) 50 ppm (restrictive limit) 50 ppm (restrictive limit) OEL chemical category Risk of cutaneous absorption Germany - Occupational Exposure Limits (TRGS >0 ppm (isomer mixture) 50 ppm (isomer mixture) Gibraltar - Occupational Exposure Limits OEL TWA 308 mg/m³ 50 ppm 50 ppm OEL chemical category 8kin notation Greece - Occupational Exposure Limits Greece - Occupational Exposure Limits OEL TWA 600 mg/m³ OEL TWA OEL TWA 600 mg/m³	HTP (OEL TWA)	310 mg/m³	
France - Occupational Exposure Limits VME (OEL TWA) 308 mg/m³ (restrictive limit) 50 ppm (restrictive limit) OEL chemical category Risk of cutaneous absorption Germany - Occupational Exposure Limits (TRGS 9000) AGW (OEL TWA) 310 mg/m³ (isomer mixture) 50 ppm (isomer mixture) Gibraltar - Occupational Exposure Limits OEL TWA 308 mg/m³ 50 ppm OEL chemical category Skin notation Greece - Occupational Exposure Limits OEL TWA 600 mg/m³ 100 ppm OEL STEL 900 mg/m³ 150 ppm		50 ppm	
VME (OEL TWA) 308 mg/m³ (restrictive limit) 50 ppm (restrictive limit) 50 ppm (restrictive limit) OEL chemical category Risk of cutaneous absorption Germany - Occupational Exposure Limits (TRGS 900	OEL chemical category	Potential for cutaneous absorption	
DEL chemical category Risk of cutaneous absorption AGW (OEL TWA) Bibraltar - Occupational Exposure Limits CEL TWA AGW (OEL TWA) Bibraltar - Occupational Exposure Limits CEL TWA Bibraltar - Occupational Exposure Limits OEL TWA Bibraltar - Occupational Exposure Limits OEL TWA CITY - Occupational Exposure Limits OCCUPATION - Occupational Exposure Limits OCCUPA	France - Occupational Exposure Limits		
OEL chemical category Risk of cutaneous absorption Germany - Occupational Exposure Limits (TRGS 9005) AGW (OEL TWA) 310 mg/m³ (isomer mixture) 50 ppm (isomer mixture) Gibraltar - Occupational Exposure Limits OEL TWA 308 mg/m³ 50 ppm OEL chemical category Skin notation Greece - Occupational Exposure Limits OEL TWA 600 mg/m³ 100 ppm OEL STEL 900 mg/m³ 150 ppm	VME (OEL TWA)	308 mg/m³ (restrictive limit)	
Germany - Occupational Exposure Limits (TRGS 90) AGW (OEL TWA) 310 mg/m³ (isomer mixture) 50 ppm (isomer mixture) Gibraltar - Occupational Exposure Limits OEL TWA 308 mg/m³ 50 ppm OEL chemical category Skin notation Greece - Occupational Exposure Limits OEL TWA 600 mg/m³ 100 ppm OEL STEL 900 mg/m³ 150 ppm		50 ppm (restrictive limit)	
AGW (OEL TWA) 310 mg/m³ (isomer mixture) 50 ppm (isomer mixture) Gibraltar - Occupational Exposure Limits OEL TWA 308 mg/m³ 50 ppm OEL chemical category Skin notation Greece - Occupational Exposure Limits OEL TWA 600 mg/m³ 100 ppm OEL STEL 900 mg/m³ 150 ppm	OEL chemical category	Risk of cutaneous absorption	
Gibraltar - Occupational Exposure Limits OEL TWA 308 mg/m³ 50 ppm OEL chemical category Skin notation Greece - Occupational Exposure Limits OEL TWA 600 mg/m³ 100 ppm OEL STEL 900 mg/m³ 150 ppm	Germany - Occupational Exposure Limits (TRGS 9	00)	
Gibraltar - Occupational Exposure Limits OEL TWA 308 mg/m³ 50 ppm OEL chemical category Skin notation Greece - Occupational Exposure Limits OEL TWA 600 mg/m³ 100 ppm OEL STEL 900 mg/m³ 150 ppm	AGW (OEL TWA)	310 mg/m³ (isomer mixture)	
OEL TWA 308 mg/m³ 50 ppm OEL chemical category Skin notation Greece - Occupational Exposure Limits OEL TWA 600 mg/m³ 100 ppm OEL STEL 900 mg/m³ 150 ppm		50 ppm (isomer mixture)	
OEL chemical category Skin notation Greece - Occupational Exposure Limits OEL TWA 600 mg/m³ 100 ppm OEL STEL 900 mg/m³ 150 ppm	Gibraltar - Occupational Exposure Limits		
OEL chemical category Skin notation Greece - Occupational Exposure Limits OEL TWA 600 mg/m³ 100 ppm OEL STEL 900 mg/m³ 150 ppm	OEL TWA	308 mg/m³	
Greece - Occupational Exposure Limits OEL TWA 600 mg/m³ 100 ppm 100 mg/m³ OEL STEL 900 mg/m³ 150 ppm		50 ppm	
OEL TWA 600 mg/m³ 100 ppm OEL STEL 900 mg/m³ 150 ppm	OEL chemical category	Skin notation	
DEL STEL 900 mg/m³ 150 ppm			
OEL STEL 900 mg/m³ 150 ppm	OEL TWA	600 mg/m³	
150 ppm		100 ppm	
	OEL STEL	900 mg/m³	
OEL chemical category skin - potential for cutaneous absorption		150 ppm	
	OEL chemical category	skin - potential for cutaneous absorption	

Safety Data Sheet

Dipropylene glycol monomethyl ether (34590-94-8)	
Hungary - Occupational Exposure Limits	
AK (OEL TWA)	308 mg/m³
Ireland - Occupational Exposure Limits	
OEL TWA	308 mg/m³ ((2-Methoxymethylethoxy)propanol)
	50 ppm ((2-Methoxymethylethoxy)propanol)
OEL STEL	924 mg/m³ (calculated (2-(2-Methoxypropoxy)-1-propanol)
	150 ppm (calculated (2-(2-Methoxypropoxy)-1-propanol)
OEL chemical category	Potential for cutaneous absorption
Italy - Occupational Exposure Limits	
OEL TWA	308 mg/m³
	50 ppm
OEL chemical category	skin - potential for cutaneous absorption
Latvia - Occupational Exposure Limits	
OEL TWA	308 mg/m³
	50 ppm
OEL chemical category	skin - potential for cutaneous exposure
Lithuania - Occupational Exposure Limits	
IPRV (OEL TWA)	300 mg/m³ (2-(2-Methoxypropoxy)-propanol)
	50 ppm (2-(2-Methoxypropoxy)-propanol)
TPRV (OEL STEL)	450 mg/m³ (2-(2-Methoxypropoxy)-propanol)
	75 ppm (2-(2-Methoxypropoxy)-propanol)
OEL chemical category	Skin notation
Luxembourg - Occupational Exposure Limits	
OEL TWA	308 mg/m³
	50 ppm
OEL chemical category	Possibility of significant uptake through the skin
Malta - Occupational Exposure Limits	
OEL TWA	308 mg/m³
	50 ppm
OEL chemical category	Possibility of significant uptake through the skin
Netherlands - Occupational Exposure Limits	
TGG-8u (OEL TWA)	300 mg/m³
	48.7 ppm
Poland - Occupational Exposure Limits	
NDS (OEL TWA)	240 mg/m³ (mixture of isomers: 1-(2-Methoxy-1-methylethoxy)propan-2-ol, 1-(2-Methoxy-2-methylethoxy)propan-1-ol)
NDSCh (OEL STEL)	480 mg/m³ (mixture of isomers: 1-(2-Methoxy-1-methylethoxy)propan-2-ol, 1-(2-Methoxy-2-methylethoxy)propan-2-ol, 2-(2-Methoxy-1-methylethoxy)propan-1-ol)
Portugal - Occupational Exposure Limits	

Safety Data Sheet

Dipropylene glycol monomethyl ether (34590-94-8)	
	50 ppm (indicative limit value)
OEL STEL	150 ppm
OEL chemical category	skin - potential for cutaneous exposure indicative limit value
Romania - Occupational Exposure Limits	
OEL TWA	308 mg/m³
	50 ppm
OEL chemical category	Skin notation
Slovakia - Occupational Exposure Limits	
NPHV (OEL TWA)	308 mg/m³
	50 ppm
OEL chemical category	Potential for cutaneous absorption
Slovenia - Occupational Exposure Limits	
OEL TWA	308 mg/m³
	50 ppm
OEL STEL	308 mg/m³
	50 ppm
OEL chemical category	Potential for cutaneous absorption
Spain - Occupational Exposure Limits	
VLA-ED (OEL TWA)	308 mg/m³ (indicative limit value)
	50 ppm (indicative limit value)
OEL chemical category	skin - potential for cutaneous absorption
Sweden - Occupational Exposure Limits	
NGV (OEL TWA)	300 mg/m³
	50 ppm
KGV (OEL STEL)	450 mg/m³
	75 ppm
OEL chemical category	Skin notation
United Kingdom - Occupational Exposure Limits	
WEL TWA (OEL TWA)	308 mg/m³
	50 ppm
WEL STEL (OEL STEL)	924 mg/m³ (calculated)
	150 ppm (calculated)
WEL chemical category	Potential for cutaneous absorption
Norway - Occupational Exposure Limits	·
Grenseverdi (OEL TWA)	300 mg/m³
	50 ppm
Korttidsverdi (OEL STEL)	375 mg/m³ (value calculated)
	75 ppm (value calculated)
OEL chemical category	Skin notation

Safety Data Sheet

Dipropylene glycol monomethyl ether (34590-94-8)		
Switzerland - Occupational Exposure Limits		
MAK (OEL TWA)	300 mg/m³ (aerosol, vapour)	
	50 ppm (aerosol, vapour)	
KZGW (OEL STEL)	300 mg/m³ (aerosol, vapour)	
	50 ppm (aerosol, vapour)	
USA - ACGIH - Occupational Exposure Limits		
ACGIH OEL TWA	50 ppm (Dipropylene glycol methyl ether)	
benzaldehyde (100-52-7)		
Bulgaria - Occupational Exposure Limits		
OEL TWA	5 mg/m³	
Finland - Occupational Exposure Limits		
HTP (OEL TWA)	4.4 mg/m³	
	1 ppm	
HTP (OEL C)	17.4 mg/m³	
	4 ppm	
Hungary - Occupational Exposure Limits		
AK (OEL TWA)	5 mg/m³	
CK (OEL STEL)	10 mg/m³	
Latvia - Occupational Exposure Limits		
OEL TWA	5 mg/m³	
Lithuania - Occupational Exposure Limits		
IPRV (OEL TWA)	5 mg/m³	
Poland - Occupational Exposure Limits		
NDS (OEL TWA)	10 mg/m³	
NDSCh (OEL STEL)	40 mg/m³	
1,2-Propanediol (57-55-6)		
Croatia - Occupational Exposure Limits		
GVI (OEL TWA)	474 mg/m³ (total vapor and particles) 10 mg/m³ (particles)	
	150 ppm	
Ireland - Occupational Exposure Limits		
OEL TWA	10 mg/m³ (particulate) 470 mg/m³ (total vapour and particulates)	
	150 ppm (total vapour and particulates)	
OEL STEL	1410 mg/m³ (calculated-particulates) 30 mg/m³ (calculated)	
	450 ppm (calculated-total vapor and particulates)	
Latvia - Occupational Exposure Limits		
OEL TWA	7 mg/m³	

Safety Data Sheet

1,2-Propanediol (57-55-6)	
Lithuania - Occupational Exposure Limits	
IPRV (OEL TWA)	7 mg/m³
Poland - Occupational Exposure Limits	
NDS (OEL TWA)	100 mg/m³ (vapor and inhalable fraction)
United Kingdom - Occupational Exposure Limits	
WEL TWA (OEL TWA)	474 mg/m³ (total vapour and particulate) 10 mg/m³ (particulate)
	150 ppm (total vapour and particulate)
WEL STEL (OEL STEL)	1422 mg/m³ (calculated-total vapour and particulate) 30 mg/m³ (calculated-particulate)
	450 ppm (calculated-total vapour and particulate)
Norway - Occupational Exposure Limits	
Grenseverdi (OEL TWA)	79 mg/m³
	25 ppm
Korttidsverdi (OEL STEL)	118.5 mg/m³ (value calculated)
	37.5 ppm (value calculated)
isopentyl acetate (123-92-2)	
EU - Indicative Occupational Exposure Limit (IOEL)	
IOEL TWA	270 mg/m³
	50 ppm
IOEL STEL	540 mg/m³
	100 ppm
Austria - Occupational Exposure Limits	
MAK (OEL TWA)	270 mg/m³ (Pentyl acetate (all isomers))
	50 ppm (Pentyl acetate (all isomers))
MAK (OEL STEL)	540 mg/m³ (Pentylacetate)
	100 ppm (Pentylacetate)
Belgium - Occupational Exposure Limits	
OEL TWA	270 mg/m³
	50 ppm
OEL STEL	540 mg/m³
	100 ppm
Bulgaria - Occupational Exposure Limits	
OEL TWA	270 mg/m³
	50 ppm
OEL STEL	540 mg/m³
	100 ppm
Croatia - Occupational Exposure Limits	
GVI (OEL TWA)	270 mg/m³

Safety Data Sheet

isopentyl acetate (123-92-2)			
	50 ppm		
KGVI (OEL STEL)	540 mg/m³		
	100 ppm		
Cyprus - Occupational Exposure Limits			
OEL TWA	270 mg/m³		
	50 ppm		
OEL STEL	540 mg/m³		
	100 ppm		
Denmark - Occupational Exposure Limits			
OEL TWA	271 mg/m³ (Amyl acetate, all isomers)		
	50 ppm (Amyl acetate, all isomers)		
OEL STEL	540 mg/m³		
	100 ppm		
Estonia - Occupational Exposure Limits			
OEL TWA	270 mg/m³		
	50 ppm		
OEL STEL	540 mg/m³		
	100 ppm		
Finland - Occupational Exposure Limits			
HTP (OEL TWA)	270 mg/m³ (Pentyl acetate)		
	50 ppm (Pentyl acetate)		
HTP (OEL STEL)	540 mg/m³		
	100 ppm		
France - Occupational Exposure Limits			
VME (OEL TWA)	270 mg/m³ (restrictive limit)		
	50 ppm (restrictive limit)		
VLE (OEL C/STEL)	540 mg/m³ (restrictive limit)		
	100 ppm (restrictive limit)		
Germany - Occupational Exposure Limits (TRGS 90	00)		
AGW (OEL TWA)	270 mg/m³		
	50 ppm		
Gibraltar - Occupational Exposure Limits	Gibraltar - Occupational Exposure Limits		
OEL TWA	270 mg/m³		
	50 ppm		
OEL STEL	540 mg/m³		
	100 ppm		
Greece - Occupational Exposure Limits			
OEL TWA	530 mg/m³		
	100 ppm		

Safety Data Sheet

isopentyl acetate (123-92-2)		
OEL STEL	800 mg/m³	
	150 ppm	
Hungary - Occupational Exposure Limits		
AK (OEL TWA)	270 mg/m³	
CK (OEL STEL)	540 mg/m³	
Ireland - Occupational Exposure Limits		
OEL TWA	260 mg/m³	
	50 ppm	
OEL STEL	520 mg/m³	
	100 ppm	
Italy - Occupational Exposure Limits		
OEL TWA	270 mg/m³	
	50 ppm	
OEL STEL	540 mg/m³	
	100 ppm	
Latvia - Occupational Exposure Limits		
OEL TWA	270 mg/m³	
	50 ppm	
Lithuania - Occupational Exposure Limits		
IPRV (OEL TWA)	270 mg/m³	
	50 ppm	
TPRV (OEL STEL)	540 mg/m³	
	100 ppm	
Luxembourg - Occupational Exposure Limits		
OEL TWA	270 mg/m³	
	50 ppm	
OEL STEL	540 mg/m³	
	100 ppm	
Malta - Occupational Exposure Limits		
OEL TWA	270 mg/m³	
	50 ppm	
OEL STEL	540 mg/m³	
	100 ppm	
Netherlands - Occupational Exposure Limits		
TGG-15min (OEL STEL)	530 mg/m³	
	98.1 ppm	
Poland - Occupational Exposure Limits		
NDS (OEL TWA)	250 mg/m³	
NDSCh (OEL STEL)	500 mg/m³	

Safety Data Sheet

isopentyl acetate (123-92-2)		
Portugal - Occupational Exposure Limits		
OEL TWA	270 mg/m³ (indicative limit value)	
	50 ppm (indicative limit value (Pentyl acetate, all isomers)	
OEL STEL	540 mg/m³ (indicative limit value)	
	100 ppm (indicative limit value)	
Romania - Occupational Exposure Limits		
OEL TWA	270 mg/m³	
	50 ppm	
OEL STEL	540 mg/m³	
	100 ppm	
Slovakia - Occupational Exposure Limits		
NPHV (OEL TWA)	270 mg/m³	
	50 ppm	
NPHV (OEL C)	540 mg/m³	
Slovenia - Occupational Exposure Limits		
OEL TWA	270 mg/m³	
	50 ppm	
OEL STEL	540 mg/m³	
	100 ppm	
Spain - Occupational Exposure Limits		
VLA-ED (OEL TWA)	270 mg/m³ (indicative limit value)	
	50 ppm (indicative limit value)	
VLA-EC (OEL STEL)	540 mg/m³	
	100 ppm	
Sweden - Occupational Exposure Limits		
NGV (OEL TWA)	270 mg/m³ (Pentyl acetates)	
	50 ppm (Pentyl acetates)	
KGV (OEL STEL)	540 mg/m³ (Pentyl acetates)	
	100 ppm (Pentyl acetates)	
Norway - Occupational Exposure Limits		
Grenseverdi (OEL TWA)	260 mg/m³	
	50 ppm	
Korttidsverdi (OEL STEL)	325 mg/m³ (value calculated)	
	75 ppm (value calculated)	
Switzerland - Occupational Exposure Limits		
MAK (OEL TWA)	260 mg/m³ (Pentyl acetate all isomers)	
	50 ppm (Pentyl acetate all isomers)	
KZGW (OEL STEL)	260 mg/m³ (Pentyl acetate all isomers)	
	50 ppm (Pentyl acetate all isomers)	
	1	

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

isopentyl acetate (123-92-2)	
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL TWA	50 ppm (Pentyl acetate, all isomers)
ACGIH OEL STEL	100 ppm (Pentyl acetate, all isomers)

8.2. Exposure controls

Appropriate engineering controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

Personal protection equipment

Personal protective equipment:

Avoid all unnecessary exposure.

Personal protective equipment symbol(s):





Eye and face protection

Eye protection:

Chemical goggles or safety glasses. Safety glasses

Skin protection

Skin and body protection:

Wear suitable protective clothing

Hand protection:

Wear protective gloves.

Respiratory protection

Respiratory protection:

Wear appropriate mask

Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment.

Other information:

Viscosity, kinematic

Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid

Colour : Conforms to standard.

Odour characteristic. Odour threshold : Not available Melting point : Not applicable Freezing point : Not available Boiling point : Not available Flammability : Not applicable Lower explosion limit : Not available Upper explosion limit : Not available Flash point : > 93 °C Auto-ignition temperature : Not available Decomposition temperature : Not available pΗ : Not available

5/1/2025 (Revision date) EN (English) 21/33

: Not available

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Solubility : Not available Partition coefficient n-octanol/water (Log Kow) : Not available

Vapour pressure : 0.001209329 mm Hg (calculated value)

Vapour pressure at 50°C : Not available
Density : Not available
Relative density : Not available
Relative vapour density at 20°C : Not available
Particle characteristics : Not applicable

9.2. Other information

Other safety characteristics

VOC content : 3.7727725 % (calculated value)(CARB VOC) (%w/w)

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Not established.

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures.

10.5. Incompatible materials

Strong acids. Strong bases.

10.6. Hazardous decomposition products

fume. Carbon monoxide. Carbon dioxide.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Harmful if swallowed.

Acute toxicity (dermal) : Not classified

Acute toxicity (inhalation) : Not classified

SALTED CARAMEL #EU55145F	
ATE CLP (oral)	640.205 mg/kg bodyweight
benzyl benzoate (120-51-4)	
LD50 oral rat	> 2000 mg/kg (Source: ECHA_API)
LD50 oral	1160 mg/kg bodyweight
LD50 dermal rabbit	4000 mg/kg (Source: NLM_CIP)
Cinnamic aldehyde (104-55-2)	
LD50 oral rat	2220 mg/kg (Source: NLM_CIP)
LD50 oral	2220 mg/kg
LD50 dermal rabbit	1260 mg/kg (Source: EPA_HPV)

Safety Data Sheet

Cinnamic aldehyde (104-55-2)			
LD50 dermal	1260 mg/kg		
Vanillin (121-33-5)			
LD50 dermal rabbit	> 5010 mg/kg (Source: OECD_SIDS)		
LD50 dermal	2600 mg/kg bodyweight		
Ethyl vanillin (121-32-4)			
LD50 oral rat	1590 mg/kg (Source: NLM_CIP)		
LD50 oral	3000 mg/kg bodyweight		
LD50 dermal rat	> 2000 mg/kg (Source: ECHA_API)		
1,2-Cyclopentanedione, 3-methyl- (765-70-8)			
LD50 oral	1067 mg/kg bodyweight		
Veratryl aldehyde (Veratraldehyde) (120-14-9)			
LD50 oral rat	2 g/kg (Source: NLM_CIP)		
LD50 oral	2000 mg/kg bodyweight		
Toluene (108-88-3)			
LD50 oral rat	2600 mg/kg (Source: JAPAN_GHS)		
LD50 dermal rabbit	12000 mg/kg (Source: JAPAN_GHS)		
LC50 Inhalation - Rat	12.5 mg/l/4h		
Dipropylene glycol monomethyl ether (34590-	94-8)		
LD50 oral rat	5.35 g/kg (Source: NLM_HSDB)		
LD50 dermal rabbit	9500 mg/kg (Source: NLM_CIP)		
COUMARIN (91-64-5)			
LD50 oral rat	> 5000 mg/kg (Source: JAPAN_GHS)		
LD50 dermal rat	293 mg/kg (Source: ECHA_API)		
benzaldehyde (100-52-7)			
LD50 oral rat	1292 mg/kg (Source: JAPAN_GHS)		
LD50 dermal rabbit	> 1250 mg/kg (Source: JAPAN_GHS)		
LC50 Inhalation - Rat	< 5 mg/l/4h		
1,2-Propanediol (57-55-6)			
LD50 oral rat	20 g/kg (Source: NLM_CIP)		
LD50 dermal rabbit	20800 mg/kg (Source: NLM_CIP)		
Phenylacetaldehyde (122-78-1)	Phenylacetaldehyde (122-78-1)		
LD50 oral	1550 mg/kg		
	Not classified		
	Causes serious eye irritation.		
Respiratory or skin sensitisation :	May cause an allergic skin reaction.		
Germ cell mutagenicity :	Not classified		
Carcinogenicity :	Not classified		

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Toluene (108-88-3)	
IARC group	3 - Not classifiable
COUMARIN (91-64-5)	
IARC group	3 - Not classifiable
Reproductive toxicity :	Not classified
STOT-single exposure :	Not classified
benzaldehyde (100-52-7)	
STOT-single exposure	May cause respiratory irritation.
STOT-repeated exposure :	Not classified
Aspiration hazard :	Not classified
benzyl benzoate (120-51-4)	
Viscosity, kinematic	7.456 mm ² /s
Toluene (108-88-3)	
Hydrocarbon	Yes

11.2. Information on other hazards

Other information

Potential adverse human health effects and

: Based on available data, the classification criteria are not met, Harmful if swallowed.

symptoms

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general

: Very toxic to aquatic life. Toxic to aquatic life with long lasting effects.

Hazardous to the aquatic environment, short–term

: Very toxic to aquatic life.

(acute)

Hazardous to the aquatic environment, long-term : Toxic to aquatic life with long lasting effects.

(chronic)

·		
benzyl benzoate (120-51-4)		
LC50 - Fish [1]	2.32 mg/l (Exposure time: 96 h - Species: Danio rerio [semi-static] Source: ECHA)	
NOEC (chronic)	0.168 mg/l	
Vanillin (121-33-5)		
LC50 - Fish [1]	53 – 61.3 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through] Source: EPA)	
LC50 - Fish [2]	88 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static] Source: EPA)	
NOEC (acute)	10000 mg/kg (Exposure time: 42 Days - Species: Eisenia foetida [soil dry weight])	
Ethyl vanillin (121-32-4)		
LC50 - Fish [1]	81.4 – 94.3 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through] Source: EPA)	
Toluene (108-88-3)		
LC50 - Fish [1]	15.22 – 19.05 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through] Source: EPA)	
LC50 - Fish [2]	12.6 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static] Source: EPA)	
EC50 - Crustacea [1]	5.46 – 9.83 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])	

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Toluene (108-88-3)		
EC50 - Crustacea [2]	11.5 mg/l (Exposure time: 48 h - Species: Daphnia magna)	
EC50 72h - Algae [1]	12.5 mg/l (Species: Pseudokirchneriella subcapitata [static])	
EC50 96h - Algae [1]	> 433 mg/l (Species: Pseudokirchneriella subcapitata)	
Dipropylene glycol monomethyl ether (34590-94-8)		
LC50 - Fish [1]	> 10000 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])	
EC50 - Crustacea [1]	1919 mg/l (Exposure time: 48 h - Species: Daphnia magna)	
benzaldehyde (100-52-7)		
LC50 - Fish [1]	10.6 – 11.8 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [flow-through] Source: EPA)	
LC50 - Fish [2]	12.69 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static] Source: IUCLID)	
1,2-Propanediol (57-55-6)		
LC50 - Fish [1]	51600 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static] Source: IUCLID)	
LC50 - Fish [2]	41 – 47 ml/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static] Source: EPA)	
EC50 - Crustacea [1]	> 1000 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])	
EC50 96h - Algae [1]	19000 mg/l (Species: Pseudokirchneriella subcapitata)	

12.2. Persistence and degradability

SALTED CARAMEL #EU55145F		
Not established.		
benzyl benzoate (120-51-4)		
May cause long-term adverse effects in the environment.		
Cinnamic aldehyde (104-55-2)		
Rapidly degradable		
Vanillin (121-33-5)		
Rapidly degradable		
Ethyl vanillin (121-32-4)		
Rapidly degradable		
1,2-Cyclopentanedione, 3-methyl- (765-70-8)		
Rapidly degradable		
Veratryl aldehyde (Veratraldehyde) (120-14-9)		
Rapidly degradable		
Toluene (108-88-3)		
Rapidly degradable		
Dipropylene glycol monomethyl ether (34590-94-8)		
Rapidly degradable		
COUMARIN (91-64-5)		
Rapidly degradable		

Safety Data Sheet

benzaldehyde (100-52-7)		
Persistence and degradability	Rapidly degradable	
1,2-Propanediol (57-55-6)		
Persistence and degradability	Rapidly degradable	
isopentyl acetate (123-92-2)		
Persistence and degradability	Rapidly degradable	
Phenylacetaldehyde (122-78-1)		
Persistence and degradability	Rapidly degradable	
12.3. Bioaccumulative potential		
SALTED CARAMEL #EU55145F		
Bioaccumulative potential	Not established.	
benzyl benzoate (120-51-4)		
Partition coefficient n-octanol/water (Log Pow)	3.97 (at 25 °C)	
Bioaccumulative potential	Not established.	
Cinnamic aldehyde (104-55-2)		
Partition coefficient n-octanol/water (Log Pow)	2.1065 (at 25 °C)	
Vanillin (121-33-5)		
Partition coefficient n-octanol/water (Log Pow)	1.23 (at 22 °C)	
Ethyl vanillin (121-32-4)		
Partition coefficient n-octanol/water (Log Pow)	1.61 (at 25 °C)	
1,2-Cyclopentanedione, 3-methyl- (765-70-8)		
Partition coefficient n-octanol/water (Log Pow)	-0.54 (calculated value)	
Veratryl aldehyde (Veratraldehyde) (120-14-9)		
Partition coefficient n-octanol/water (Log Pow)	0.8 (at 25 °C)	
Toluene (108-88-3)		
Partition coefficient n-octanol/water (Log Pow)	2.73 (at 20 °C (at pH 7)	
Dipropylene glycol monomethyl ether (34590-	Dipropylene glycol monomethyl ether (34590-94-8)	
Partition coefficient n-octanol/water (Log Pow)	0.35 (at 25 °C (at pH 7)	
COUMARIN (91-64-5)		
Partition coefficient n-octanol/water (Log Pow)	≥ 1.91 – ≤ 1.51 (at 25 °C (at pH 7)	
benzaldehyde (100-52-7)		
BCF - Fish [1]	(no significant bioaccumulation)	
Partition coefficient n-octanol/water (Log Pow)	1.4 (at 25 °C)	
1,2-Propanediol (57-55-6)		
BCF - Fish [1]	(1 dimensionless)	
Partition coefficient n-octanol/water (Log Pow)	-1.07 (at 20.5 °C (at pH >=6.2-<=6.4)	

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

isopentyl acetate (123-92-2)	
Partition coefficient n-octanol/water (Log Pow)	2.7 (at 35 °C)
Phenylacetaldehyde (122-78-1)	
Partition coefficient n-octanol/water (Log Pow)	1.44 (at 25 °C (at pH 6.4)

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Endocrine disrupting properties

No additional information available

12.7. Other adverse effects

SALTED CARAMEL #EU55145F	
Other information Avoid release to the environment.	
benzyl benzoate (120-51-4)	
Other information	Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods

Product/Packaging disposal recommendations

Ecological waste information HP Code

- : Dispose of contents/container in accordance with licensed collector's sorting instructions.
- : Dispose in a safe manner in accordance with local/national regulations. Dispose of contents/container in accordance with local/national laws and regulations.
- : Avoid release to the environment.
- HP6 "Acute Toxicity:" waste which can cause acute toxic effects following oral or dermal administration, or inhalation exposure.

HP14 - "Ecotoxic:" waste which presents or may present immediate or delayed risks for one or more sectors of the environment

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
14.1. UN number or ID n	umber			
UN 3082	UN 3082	UN 3082	UN 3082	UN 3082
14.2. UN proper shipping	g name			
ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Benzyl Benzoate)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Benzyl Benzoate)	Environmentally hazardous substance, liquid, n.o.s. (Benzyl Benzoate)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Benzyl Benzoate)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Benzyl Benzoate)

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

ADR	IMDG	IATA	ADN	RID		
Transport document descr	iption					
UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Benzyl Benzoate), 9, III, (-)	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Benzyl Benzoate), 9, III, MARINE POLLUTANT	UN 3082 Environmentally hazardous substance, liquid, n.o.s. (Benzyl Benzoate), 9, III N.O.S. (Benzyl Benzyl SUBSTANCE, LIQ N.O.S. (Benzyl Benzyl Ben		UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Benzyl Benzoate), 9, III		
14.3. Transport hazard	class(es)					
9	9	9	9	9		
**************************************	2	**************************************	**************************************	**************************************		
14.4. Packing group	14.4. Packing group					
III	III	III	III	III		
14.5. Environmental hazards						
Dangerous for the environment: Yes	Dangerous for the environment: Yes Marine pollutant: Yes EmS-No. (Fire): F-A EmS-No. (Spillage): S-F	Dangerous for the environment: Yes	Dangerous for the environment: Yes	Dangerous for the environment: Yes		
No supplementary information	n available					

14.6. Special precautions for user

Overland transport

Classification code (ADR) : M6

Special provisions (ADR) : 274, 335, 375, 601

Limited quantities (ADR) : 5I Excepted quantities (ADR) : E1

Packing instructions (ADR) : P001, IBC03, LP01, R001

Special packing provisions (ADR) : PP1
Mixed packing provisions (ADR) : MP19
Portable tank and bulk container instructions (ADR) : T4
Portable tank and bulk container special provisions : TP1, TP29

(ADR)

Tank code (ADR) : LGBV
Vehicle for tank carriage : AT
Transport category (ADR) : 3
Special provisions for carriage - Packages (ADR) : V12
Special provisions for carriage - Loading, unloading : CV13

and handling (ADR)

Hazard identification number (Kemler No.) : 90

Orange plates :

90 3082

Tunnel restriction code (ADR) : EAC code : •3Z

Transport by sea

Special provisions (IMDG) : 274, 335, 969

Limited quantities (IMDG) : 5 L
Excepted quantities (IMDG) : E1

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Packing instructions (IMDG) : LP01, P001
Special packing provisions (IMDG) : PP1
IBC packing instructions (IMDG) : IBC03
Tank instructions (IMDG) : T4
Tank special provisions (IMDG) : TP1, TP29
Stowage category (IMDG) : A

Air transport

PCA Excepted quantities (IATA) : E1
PCA Limited quantities (IATA) : Y964
PCA limited quantity max net quantity (IATA) : 30kgG
PCA packing instructions (IATA) : 964
PCA max net quantity (IATA) : 450L
CAO packing instructions (IATA) : 964
CAO max net quantity (IATA) : 450L

Special provisions (IATA) : A97, A158, A197, A215

ERG code (IATA) : 9L

Inland waterway transport

Classification code (ADN) : M6

Special provisions (ADN) : 274, 335, 375, 601

Limited quantities (ADN) : 5 L
Excepted quantities (ADN) : E1
Carriage permitted (ADN) : T
Equipment required (ADN) : PP
Number of blue cones/lights (ADN) : 0

Rail transport

Classification code (RID) : M6

Special provisions (RID) : 274, 335, 375, 601

Limited quantities (RID) : 5L Excepted quantities (RID) : E1

Packing instructions (RID) : P001, IBC03, LP01, R001

Special packing provisions (RID) : PP1
Mixed packing provisions (RID) : MP19
Portable tank and bulk container instructions (RID) : T4
Portable tank and bulk container special provisions : TP1, TP29

(RID)

Tank codes for RID tanks (RID) : LGBV

Transport category (RID) : 3

Special provisions for carriage – Packages (RID) : W12

Special provisions for carriage - Loading, unloading : CW13, CW31

and handling (RID)

Colis express (express parcels) (RID) : CE8
Hazard identification number (RID) : 90

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU-Regulations

REACH Annex XVII (Restriction List)

EU restriction list (REACH Annex XVII)			
Reference code	Applicable on	Entry title or description	
3(a)	Isoamyl acetate	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8 types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.14 categories 1 and 2, 2.15 types A to F	
3(b)	SALTED CARAMEL #EU55145F; Benzyl benzoate; Cinnamic aldehyde; Benzaldehyde ; Phenylacetaldehyde	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10	
3(c)	SALTED CARAMEL #EU55145F; Benzyl benzoate; Cinnamic aldehyde; Phenylacetaldehyde	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard class 4.1	
48.	Toluene	Toluene	

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (2024/590)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 2024/590 on substances that deplete the ozone layer)

Council Regulation (EC) for the control of dual-use items

Contains no substance subject to the COUNCIL REGULATION (EC) for the control of dual-use items

VOC Directive (2004/42)

VOC content : 3.7727725 % (calculated value)(CARB VOC) (%w/w)

Explosives Precursors Regulation (2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

Drug Precursors Regulation (EC 273/2004)

Contains substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

Name	CN designation	CAS-No.	CN code	Category, Subcategory	Threshold	Annex
Toluene		108-88-3	2902 30 00	Category 3		Annex I

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

National regulations

France

Occupational diseases		
Code	Description	
RG 4 BIS	Gastrointestinal disorders caused by benzene, toluene, xylenes and all products containing them	
RG 84	Conditions caused by liquid organic solvents for professional use: saturated or unsaturated aliphatic or cyclic liquid hydrocarbons and mixtures thereof; liquid halogenated hydrocarbons; nitrated derivatives of aliphatic hydrocarbons; alcohols; glycols, glycol ethers; ketones; aldehydes; aliphatic and cyclic ethers, including tetrahydrofuran; esters; dimethylformamide and dimethylacetamine; acetonitrile and propionitrile; pyridine; dimethylsulfone and dimethylsulfoxide	

Germany

VOC ordinance (ChemVOCFarbV) : VOC content 3.7727725 % (calculated value)(CARB VOC)

(%w/w)

Water hazard class (WGK) : WGK 2, Significantly hazardous to water (Classification according to AwSV, Annex 1). List of sensitizing substances (TRGS 907) Contains sensitizing substances according TRGS 907.

Major Accidents Ordinance (12. BlmSchV)

: Is not subject to the Major Accidents Ordinance (12. BlmSchV)

Netherlands

ABM category : A(1) - highly toxic for aquatic organisms, may have longterm hazardous effects in aquatic

environment

SZW-lijst van kankerverwekkende stoffen : None of the components are listed SZW-lijst van mutagene stoffen : None of the components are listed

SZW-lijst van reprotoxische stoffen – Borstvoeding : None of the components are listed

SZW-lijst van reprotoxische stoffen -: None of the components are listed

Vruchtbaarheid SZW-lijst van reprotoxische stoffen - Ontwikkeling : Toluene is listed

Classification remarks : Emergency management guidelines for the storage of flammable liquids must be followed

Danish National Regulations Young people below the age of 18 years are not allowed to use the product

Pregnant/breastfeeding women working with the product must not be in direct contact with

the product

Denmark

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Poland

Polish National Regulations

: Act of 25 February 2011 on chemical substances and their mixtures (J. o L. No. 63, item 322 as amended; consolidated text J. o L. 2019, item 1225).

Act of 14 December 2012 on waste (J. o L. 2013, item 322 as amended; consolidated text J. o L. 2020, item 797).

The announcement of Marshal of the Sejm of the Republic of Poland dated 19 October 2016 concerning the consolidated text announcement of the decree on the management of packaging and packaging waste (J. o L. 2016, item 1863 as amended).

Decree of the Minister of Environment of 14 December 2014 on the catalogue of waste (J. o L. 2014, item 1923).

Act of 19 August 2011 on the Carriage of Dangerous Goods (J. o L. 2011 No. 227, item 1367 as amended; consolidated text J. o L. 2020, item 154).

Regulation of the Minister of Family, Labour and Social Policy of 12 June 2018 on the highest permissible concentration and intensity of noxious agents for health at work environment (J. o L. item 1286 as amended).

The announcement of Minister of Health dated 9 September 2016 concerning the consolidated text announcement of the decree of the Minister of Health of 30 December 2004 on health and safety at work related to exposure to chemical agents at work (J. o L. of 16 September 2016, item 1488)

Regulation of the Minister of Health of 2 February 2011 on tests and measurements of the noxious agents for health at work environment (J. o L. No. 33, item 166 as amended). Regulation of the Minister of Environment of 9 December 2003 on particularly hazardous substances to the environment (J. o L. No. 217, item 2141).

ADR Agreement: Government Statement of 13 March 2023 on the entry into force of amendments to Annexes A and B to the Agreement concerning the International Carriage of Dangerous Goods by Road (ADR), signed in Geneva on 30 September 1957 (J. o. L. 2023, item 891)

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Other information : None.

Full text of H- and EUH-statements:		
Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4	
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4	
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4	
Aquatic Acute 1	Hazardous to the aquatic environment – Acute Hazard, Category 1	
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2	
Aquatic Chronic 3	Hazardous to the aquatic environment – Chronic Hazard, Category 3	
EUH208	Contains {0 message≤name of sensitising substance> fieldvalue=_SENSITIZER_COMPONENTS}. May produce an allergic reaction.	
Eye Dam. 1	Serious eye damage/eye irritation, Category 1	
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2	
Flam. Liq. 3	Flammable liquids, Category 3	
Repr. 2	Reproductive toxicity, Category 2	
Skin Corr. 1B	Skin corrosion/irritation, Category 1, Sub-Category 1B	
Skin Irrit. 2	Skin corrosion/irritation, Category 2	
Skin Sens. 1	Skin sensitisation, Category 1	

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Full text of H- and EUH-statements:		
Skin Sens. 1A	Skin sensitisation, category 1A	
Skin Sens. 1B	Skin sensitisation, category 1B	
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Respiratory tract irritation	
H226	Flammable liquid and vapour.	
H302	Harmful if swallowed.	
H312	Harmful in contact with skin.	
H314	Causes severe skin burns and eye damage.	
H315	Causes skin irritation.	
H317	May cause an allergic skin reaction.	
H318	Causes serious eye damage.	
H319	Causes serious eye irritation.	
H332	Harmful if inhaled.	
H335	May cause respiratory irritation.	
H361	Suspected of damaging fertility or the unborn child.	
H400	Very toxic to aquatic life.	
H411	Toxic to aquatic life with long lasting effects.	
H412	Harmful to aquatic life with long lasting effects.	

The classification complies with

: ATP 12

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.